Lexmark™

# Lexmark XC9525

**Versatile. Simple. Sustainable.**

ENERGY STAR

epeat SILVER

Works with Apple AirPrint

mopria

IPP Everywhere™

Unisor TONER

# Lexmark XC9525

With the new XC9525 color A3 multifunction printer, you get reassuring versatility, exceptional sustainability, and surprising simplicity from such sophisticated technology. Boost your productivity with vivid prints — up to 25 pages per minute*. Intuitively navigate the 10-inch (25 cm) color touchscreen, and save time with single-pass two-sided scanning. Effortlessly create everything your business requires, and custom configure your multifunction printer with interchangeable options tailored to your needs.

## Versatile: Easy to Use

**Create everything your business requires and anything you can imagine** — from standard office documents to marketing brochures, booklets and posters — with broad media size support, high-volume printing, and exceptional paper handling and finishing capabilities.

**Print vivid, colorful visualizations, charts and documents** with professional color features (including PANTONE® calibration) and a full range of media sizes so you can effectively communicate your ideas.

**Easily incorporate your multifunction printer into your workspace** with a versatile, configurable design that saves space without sacrificing performance.

**Boost your productivity** with our rich suite of cutting-edge software and solutions with broad capabilities including scanning paper files directly into your cloud-based storage systems and automatically translating documents into 100+ languages.

**Further your organization's digital transformation** with direct integration into your critical workflows and core business systems using these IoT-enabled devices.

## Simple: Easy to Manage

**Quickly do what you need to do** using an intuitive operator panel and easy-to-follow navigation.

**Easily maintain your devices** with one-handed toner replacement, easy-to-reach serviceable areas, and alerts that are simple to understand.

**Enjoy the peace of mind of knowing you are protected** by the industry's most comprehensive security portfolio, right out of the box.

**Keep your business running** with exceptional reliability, industry-leading durability, and long-lasting toner and supplies.

**Rest easy that every aspect of your device is made to work together seamlessly** thanks to Lexmark's core technology ownership.

## Sustainable: Easy to feel good about

**Feel good about your purchase and help meet your own sustainability goals** with our world-class practices and independent third-party certifications.

**Do your part for the planet** with our industry-leading use of post-consumer recycled materials and our award-winning cartridge recycling program.

**Save energy — and money** — with technology that exceeds strict global standards for energy efficiency.

**Minimize your impact on the environment** with a company that focuses on sustainability throughout the product lifecycle from design through use, end of life and beyond.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.
** Fax icon shown on the operator panel when Fax Server is enabled, Fax Over IP is configured, etherFAX is configured, or an optional Analog Modem is installed.

# Lexmark XC9525

1 **Multifunction product with 10-inch (25 cm) touch screen**
31.9 x 23.3 x 26.0 in.
809 x 592 x 660 mm

2 **500-Sheet output bin**
Dimensions included as part of base model

3 **150-Sheet multipurpose feeder**
Dimensions included as part of base model

4 **550-Sheet tray**
Dimensions included as part of base model

5 **550-Sheet Tray**
6.4 x 23.1 x 25.6 in.
163 x 587 x 649 mm

6 **2 x 550-Sheet Tray**
12.4 x 23.1 x 25.6 in.
314 x 587 x 649 mm

7 **2000-Sheet Tandem Tray - Letter**
12.4 x 23.1 x 25.6 in.
314 x 587 x 649 mm

8 **Cabinet**
9.7 x 23.1 x 26.0 in.
247 x 587 x 660 mm

9 **1500-Sheet High-Capacity Tray**
11.4 x 13.5 x 21.4 in.
290 x 342 x 545 mm

10 **Paper Transport**
5.6 x 16.2 x 18.3 in.
143 x 412 x 466 mm

11 **Folding Paper Transport**
7.2 x 24.1 x 21.9 in.
184 x 612 x 555 mm

12 **500-Sheet Staple Finisher**
5.9 x 21.5 x 20.6 in.
150 x 546 x 523 mm

13 **Offset Stacker**
4.2 x 16.5 x 19.3 in.
107 x 420 x 489 mm

14 **1250-Sheet Staple 2/3 Hole Punch Finisher**
39.2 x 22.6 x 24.0 in.
995 x 575 x 610 mm

15 **2250-Sheet Booklet Staple 2/3 Hole Punch Finisher**
39.2 x 25.6 x 24.1 in.
995 x 650 x 613 mm

Standard

Optional

| P/N | Hardware |
|---|---|
| 20L9000 | Lexmark XC9525 |

| P/N | Supplies |
|---|---|
| 20L7500 | Staple Cartridges (4 pack) |
| 24B7574 | Lexmark XC9525, 9535, 8355 Cyan Return Program 46.9K Toner Cartridge |
| 24B7575 | Lexmark XC9525, 9535, 8355 Magenta Return Program 46.9K Toner Cartridge |
| 24B7576 | Lexmark XC9525, 9535, 8355 Yellow Return Program 46.9K Toner Cartridge |
| 24B7577 | Lexmark XC9525, 9535, 8355 Black Return Program 47.7K Toner Cartridge |
| 25A0013 | Lexmark 3-Pack 15K Finisher Staples |
| 77L0W00 | Lexmark CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355 120K Waste Container |
| 77L0Z10 | Lexmark MX953, CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355 Black 225K Imaging Unit |
| 77L0Z50 | Lexmark CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355 4- Color 250K Imaging Unit |
| 77L0ZK0 | Lexmark MX953, CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355 Black Return Program 225K Imaging Unit |
| 77L0ZV0 | Lexmark CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635,9645, 9655, 8355 4- Color Return Program 250K Imaging Unit |
| 79L0H10 | Lexmark CX950, 951, 833, XC9525, 9535, 8355 Black 47.7K Toner Cartridge |
| 79L0H20 | Lexmark CX950, 951, 833, XC9525, 9535, 8355 Cyan 46.9K Toner Cartridge |
| 79L0H30 | Lexmark CX950, 951, 833, XC9525, 9535, 8355 Magenta 46.9K Toner Cartridge |
| 79L0H40 | Lexmark CX950, 951, 833, XC9525, 9535, 8355 Yellow 46.9K Toner Cartridge |

| P/N | Paper Handling |
|---|---|
| 20L8800 | 550-Sheet Tray |
| 20L8801 | 2 x 550-Sheet Tray |
| 20L8802 | 2000-Sheet Tandem Tray - A4 |
| 20L8803 | 2000-Sheet Tandem Tray - Letter |
| 20L8804 | 1500-Sheet High-Capacity Tray |
| 20L8810 | 500-Sheet Staple Finisher |
| 20L8811 | Folding Paper Transport |
| 20L8812 | 1250-Sheet Staple 2/3 Hole Punch Finisher |
| 20L8813 | 1250-Sheet Staple 2/4 Hole Punch Finisher |
| 20L8814 | 2250-Sheet Booklet Staple 2/3 Hole Punch Finisher |
| 20L8815 | 2250-Sheet Booklet Staple 2/4 Hole Punch Finisher |
| 20L8816 | Offset Stacker |
| 20L8817 | Paper Transport |

| P/N | Memory Options |
|---|---|
| 27X0420 | 500GB Hard Disk Drive (SATA) |
| 57X0070 | Removable Hard Disk Enclosure Kit |

| P/N | Application Solutions |
|---|---|
| 57X0225 | Desktop Contactless Reader |

| | |
|---|---|
| 57X0235 | Contactless Front Solutions Module (Primary) |
| 57X0300 | Contact Authentication Device |
| 57X0301 | Contactless Authentication Device |
| 82S1203 | IPDS License |
| 82S1204 | Bar Code License |

| P/N | Connectivity |
|---|---|
| 1021231 | Parallel Cable (10-foot) |
| 1021294 | USB Cable (2-meter) |
| 14F0100 | RS-232C Serial Interface Card |
| 27X0142 | Lexmark MarkNet™ N8230 Fiber Ethernet Print Server |
| 37X6146 | MarkNet N8210 v.34 Fax Card |
| 57X7040 | English Keyboard Kit |
| SPD0001 | Surge Protective Device, 110-120V |

| P/N | Furniture |
|---|---|
| 20L8806 | Cabinet |
| 20L8807 | Keyboard Shelf |

You can install one 550-Sheet tray.
You can install one 2x550-Sheet tray, one 2,000-Sheet tandem tray or one Cabinet, but you must also install one 550-Sheet tray above it.
You can install one 1,500-Sheet high-capacity tray, but you must install one 2x550-Sheet tray or one 2,000-Sheet tandem tray beside it.
You can install one 500-Sheet staple finisher, one Offset stacker or one Folding paper transport unit.
You can install one 1,250-Sheet staple hole punch finisher or one 2,250-Sheet booklet staple hole punch finisher, but you must also install a Paper transport unit or Folding paper transport unit, one 550-Sheet tray, and one 2x550-Sheet tray or one 2,000-Sheet tandem tray or one Cabinet.

| Product Specifications | Lexmark XC9525 |
|---|---|
| **Printing** | |
| Display | Lexmark e-Task 10-inch (25 cm) class color touch screen |
| Print Speed | Up to: Black: 25 ppm [1] (Letter) / Color: 25 ppm [1] (Letter) |
| Time to First Page | As fast as: Black: TBD seconds / Color: TBD seconds |
| Print Resolution | Black: 1200 x 1200 dpi, 4800 Color Quality / Color: 4800 Color Quality, 1200 x 1200 dpi |
| Memory | Standard: 4 GB / Maximum: 4 GB |
| Hard Disk | Intelligent Storage Drive included; Magnetic Hard Disk available |
| Recommended Monthly Page Volume | 4,000 - 20,000 pages [2] |
| Maximum Monthly Duty Cycle | Up to: 100 000 pages per month [3] |
| **Copying** | |
| Copy Speed | Up to: Black: 25 cpm [1] (Letter) / Color: 25 cpm [1] (Letter) |
| Time to First Copy | As fast as: Black: TBD seconds / Color: TBD seconds |
| **Scanning** | |
| Scanner Type / ADF Scan | Flatbed scanner with automatic document feeder / DADF (single pass Duplex) |
| A4/Ltr Duplex Scan Speed | Up to: Black: 200/200 sides per minute / Color: 200/200 sides per minute |
| A4/Ltr Simplex Scan Speed | Up to: Black: 100/100 sides per minute / Color: 100/100 sides per minute |
| ADF Paper Input Capacity | Up to: 200 pages 20 lb or 75 gsm bond |
| **Supplies [4]** | |
| Laser Cartridge Yields | up to: 46,900 [5]-page Color (CMY) Cartridges / up to: 47,700 [5]-page Black Cartridge |
| Imaging Unit Estimated Yield | Up to: 225,000 (black) and 250,000 (color) pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage |
| **Paper Handling** | |
| Included Paper Handling | 500-Sheet Output Bin, 550-Sheet Tray, 150-Sheet Multipurpose Feeder |
| Optional Paper Handling | 2,250-Sheet Booklet Staple Hole Punch Finisher, 500-Sheet Staple Offset Finisher, Folding Paper Transport Unit, 1,250-Sheet Staple Hole Punch Finisher, Offset Stacker, 1,500-Sheet High-Capacity Tray, Paper Transport Unit, 2000-Sheet Tandem Tray, Cabinet, 2 x 550-Sheet Tray, 550-Sheet Tray |
| Paper Input Capacity | Up to: Standard: 700 pages 20 lb or 75 gsm bond / Maximum: 4750 pages 20 lb or 75 gsm bond |
| Paper Output Capacity | Up to: Standard: 500 pages 20 lb or 75 gsm bond / Maximum: 2650 pages 20 lb or 75 gsm bond |
| Media Types Supported | Vinyl Labels, Labels, Card Stock, Plain Paper, Envelopes, Glossy Paper, Refer to the Paper & Specialty Media Guide |
| Media Sizes Supported | A6, Oficio, 7 3/4 Envelope, JIS-B4, 9 Envelope, JIS-B5, A3, Ledger, A4, Legal, SRA3, A5, Hagaki Card, Letter, B5 Envelope, C4 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope |
| **General Information** | |
| Standard Ports | Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0 Specification Hi-Speed Certified (Type B) |
| Optional Network Ports / Optional Local Ports | MarkNet N8230 Fiber Ethernet Print Server / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial |
| Noise Level | Operating: TBD dBA (Print) / TBD dBA (Copy) / TBD dBA (Scan) |
| Specified Operating Environment | Altitude: 0 - 2896 Meters (9,500 Feet) / Humidity: 15 to 80% Relative Humidity / Temperature: 10 to 32.2°C (50 to 90°F) |
| Limited Warranty | See Statement of Limited Warranty: 1-Year Onsite Repair, Next Business Day |
| Size / Weight | H x W x D: 31.9 x 23.3 x 26.0 in. / TBD lb. |
| ENERGY STAR Typical Electricity Consumption | TEC: TBD kilowatt-hours per week |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

[1] Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. [2] "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. [3] "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. [4] Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. [5] Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2024 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http://www.openssl.org/).

lexmark.com